



Fluorescent Colors

Semi-transparent oil based flat paints with sparkling color clarity for interior or short-term exterior use.



Features & Benefits

- Strong adhesion
- Fast drying
- Dark, opaque backgrounds or outline colors can be cut into the copy line for sharp detail and maximum contrast after the colors have top dried.
- Exceptional blacklight effect.

Compatible Surfaces

Paper, board, wood, metal and certain plastics

Directions For Use



Surface Preparation:

- Apply over clean, dry surfaces which are free from wax, grease, dust, chalk, etc.
- Colors are brightest when applied over a white surface.



Directions For Use (Continued)



Application:

- Brush, roll, spray or airbrush.
- For increased protection against ultraviolet light, topcoat with 220-F 1-Shot Fluorescent UV Topcoat. Two coats of 220-F will produce a high gloss finish.
- Screen printing – May also be applied by screen printing over white substrate including paper, board, wood, metal and certain plastics. Apply through No. 8 and No. 16 mesh screen. Any type of stencil may be used.
- Allow 1 hour between coats when spraying.
- For brush applications, thin to 5% with 6000 series temperature reducers, For Spray application, thin up to 15% with 1-Shot ZZ6001 Low Temperature Reducer.



Drying Times:

- Allow at least 1 hour for top drying.
- Oxidative curing for 1-2 days is recommended.
- When spraying, allow 5 minutes drying time between passes and 1 hour setup time between coats.

Compatible Topcoats:

For increased protection against ultraviolet light, topcoat with 220-F 1-Shot Fluorescent UV Topcoat. Two coats of 220-F will produce a high gloss finish.

Equipment Cleaning:

- Clean equipment with mineral spirits
- Clean brushes with 1-Shot 4004 Brush Cleaner

Technical Data:

VOC.....	3.06-3.23 lbs/gallon
Theoretical Coverage.....	804-858 square feet at 1 mil 100% transfer
Solid by Weight.....	62.01-64.00
Solid by Volume.....	50.15-53.48

Important:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

Emergency Medical or Spill Control Information:

US (412) 434-4515; CANADA (514) 645-1320; Mexico 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein. If you require technical assistance, please call us toll-free 800/323-6593.